



Certifications:
n/d

ON REQUEST

Factory

Electrical Information			
Model No.	BL11	BL11	BL11
Power (±5%)	15W	20W	25W
Input Voltage	.	.	.
Power Factor	>0.9		
Driver Type	Constant current (CC)		
Control	.	.	.
Surge Protect.	.	.	.

Optic Information			
Efficacy	110 lm/W		
Luminous Flux	.	.	.
CCT	2700K, 3000K, 4000K		
CRI	Ra70 (Ra80 opt)		
Beam Angle	.	.	.

Description	Dimensions & Mount
25W zone-controllable bollard, power/CCT selectable.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> • IP66 & IK08 double protection • Up to 110 lm/W efficacy • CCT adjustable: 2700K, 3000K, 4000K • Certified: n/d 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> • Landscape Lighting • Park & City Centre Lighting • Urban & Residential Streets 	<ul style="list-style-type: none"> • 3 CCT adjustable (3000 / 4000 / 5000K) • Available: single & double module configs