



Certifications:
CE, RoHS, C-TICK, SAA

ON REQUEST

Factory

Electrical Information			
Model No.	CP01	CP01	CP01
Power (±5%)	75W	100W	120W
Input Voltage	.	.	.
Power Factor	>0.9		
Driver Type	Constant current (CC)		
Control	.	.	.
Surge Protect.	.	.	.

Optic Information			
Efficacy	150 lm/W		
Luminous Flux	.	.	.
CCT	3000K, 4000K, 5000K		
CRI	Ra70 (Ra80 opt)		
Beam Angle	.	.	.

Description	Dimensions & Mount
visual comfort canopy light with selectable power/CCT.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> • IP65 & IK08 double protection • Up to 150 lm/W efficacy • CCT adjustable: 3000K, 4000K, 5000K • Certified: CE, RoHS, C-TICK, SAA 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> • Petroleum & C-Store Lighting • Parking Garage Lighting • Transportation Lighting 	<ul style="list-style-type: none"> • 3 CCT adjustable (3000 / 4000 / 5000K) • Available: single & double module configs