



Certifications:
C3 corrosion class

ON REQUEST

Factory

Electrical Information			
Model No.	FL39	FL39	FL39
Power (±5%)	35W	100W	150W
Input Voltage	.	.	.
Power Factor	>0.9		
Driver Type	Constant current (CC)		
Control	.	.	.
Surge Protect.	.	.	.

Optic Information	
Efficacy	n/d lm/W
Luminous Flux	.
CCT	4000K (2200K, 3000K, 5000K optional)/RGB/RGBW/CCT
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
RGB/RGBW Casambi-controlled luminaire.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> IP66 & IK08 double protection Up to n/d lm/W efficacy CCT adjustable: 4000K (2200K, 3000K, 5000K) Certified: C3 corrosion class 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> Architectural Lighting Landscape Lighting Park & City Centre Lighting 	<ul style="list-style-type: none"> 3 CCT adjustable (3000 / 4000 / 5000K) Available: single & double module configs