



Certifications:
C5 anti-corrosion

ON REQUEST

Factory

Electrical Information						
Model No.	FL44	FL44	FL44	FL44	FL44	FL44
Power (±5%)	50W	100W	150W	200W	240W	300W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information						
Efficacy	150 lm/W					
Luminous Flux
CCT	3000K, 4000K, 5000K					
CRI	Ra70 (Ra80 opt)					
Beam Angle

Description	Dimensions & Mount
50-300W C5 anti-corrosion floodlight.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> • IP66 & IK08 double protection • Up to 150 lm/W efficacy • CCT adjustable: 3000K, 4000K, 5000K • Certified: C5 anti-corrosion 	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> • Seaport Lighting • Highly Corrosive Lighting • Car Parks & Plazas Lighting 	<ul style="list-style-type: none"> • 3 CCT adjustable (3000 / 4000 / 5000K) • Available: single & double module configs