



Certifications:
ENEC, NEMA

ON REQUEST

Factory

Electrical Information					
Model No.	FL48	FL48	FL48	FL48	FL48
Power (±5%)	180W	240W	300W	450W	600W
Input Voltage
Power Factor	>0.9				
Driver Type	Constant current (CC)				
Control
Surge Protect.

Optic Information					
Efficacy	150 lm/W				
Luminous Flux
CCT	3000K, 4000K, 5000K				
CRI	Ra70 (Ra80 opt)				
Beam Angle

Description	Dimensions & Mount
high-output area floodlight for sports and outdoor applications.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & IK10 double protection ● Up to 150 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: ENEC, NEMA 	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Car Parks & Plazas Lighting ● Stadium & Arenas Lighting ● Soccer & Football Lighting ● Large Area Lighting 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs