



Certifications:
n/d

ON REQUEST

Factory

Electrical Information		
Model No.	FL56	FL56
Power (±5%)	18W	36W
Input Voltage	.	.
Power Factor	>0.9	
Driver Type	Constant current (CC)	
Control	.	.
Surge Protect.	.	.

Optic Information		
Efficacy	90 lm/W	
Luminous Flux	.	.
CCT	3000K, 4000K, 5000K, RGB, RGBW	
CRI	Ra70 (Ra80 opt)	
Beam Angle	.	.

Description	Dimensions & Mount
RGB/RGBW anti-glare DMX fixture.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & IK08 double protection ● Up to 90 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K, RGB, ● Certified: n/d 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Architectural Lighting ● Landscape Lighting ● Park & City Centre Lighting 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs