



Certifications:
C4 corrosion class

ON REQUEST

Factory

Electrical Information				
Model No.	FL59	FL59	FL59	FL59
Power (±5%)	100W	150W	200W	300W
Input Voltage
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control
Surge Protect.

Optic Information	
Efficacy	70 lm/W
Luminous Flux	.
CCT	4000K (2200K, 3000K, 5000K optional)/RGB/RGBW
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
100-300W RA90 architectural floodlight with C4 anti-corrosion.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> IP66 & IK08 double protection Up to 70 lm/W efficacy CCT adjustable: 4000K (2200K, 3000K, 5000K) Certified: C4 corrosion class 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> Architectural Lighting Highly Corrosive Lighting Park & City Centre Lighting 	<ul style="list-style-type: none"> 3 CCT adjustable (3000 / 4000 / 5000K) Available: single & double module configs