



Certifications:  
C4

ON REQUEST

Factory

Electrical Information						
Model No.	FL72	FL72	FL72	FL72	FL72	FL72
Power (±5%)	50W	100W	150W	200W	240W	300W
Input Voltage	.	.	.	.	.	.
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control	.	.	.	.	.	.
Surge Protect.	.	.	.	.	.	.

Optic Information						
Efficacy	155 lm/W					
Luminous Flux	.	.	.	.	.	.
CCT	3000K, 4000K, 5000K					
CRI	Ra70 (Ra80 opt)					
Beam Angle	.	.	.	.	.	.

Description	Dimensions & Mount
C5 anti-corrosion floodlight for ports and airports.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP66 &amp; IK08 double protection</li> <li>● Up to 155 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Certified: C4</li> </ul>	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Seaport Lighting</li> <li>● Airport Lighting</li> <li>● Highly Corrosive Lighting</li> <li>● Stadium &amp; Arenas Lighting</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>