



Certifications:
C4

ON REQUEST

Factory

Electrical Information		
Model No.	FL72 LumiNova PI	FL72 LumiNova PI
Power (±5%)	300W	500W
Input Voltage	.	.
Power Factor	>0.9	
Driver Type	Constant current (CC)	
Control	.	.
Surge Protect.	.	.

Optic Information		
Efficacy	165 lm/W	
Luminous Flux	.	.
CCT	3000K, 4000K, 5000K	
CRI	Ra70 (Ra80 opt)	
Beam Angle	.	.

Description	Dimensions & Mount
C5 anti-corrosion floodlight for ports and airports.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & IK08 double protection ● Up to 165 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: C4 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Seaport Lighting ● Airport Lighting ● Highly Corrosive Lighting ● Stadium & Arenas Lighting 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs