



Certifications:
C5, 3G vibration resistance

ON REQUEST

Factory

Electrical Information						
Model No.	FL72 LumiNova	FL72 LumiNova	FL72 LumiNova	FL72 LumiNova	FL72 LumiNova	FL72 LumiNova Pr
Power (±5%)	50W	100W	150W	200W	240W	300W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information						
Efficacy	150 lm/W					
Luminous Flux
CCT	4000K, 5000K					
CRI	Ra70 (Ra80 opt)					
Beam Angle

Description	Dimensions & Mount
C5 anti-corrosion floodlight for ports and airports.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & IK08 double protection ● Up to 150 lm/W efficacy ● CCT adjustable: 4000K, 5000K ● Certified: C5, 3G vibration resistance 	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Seaport Lighting ● Airport Lighting ● Highly Corrosive Lighting ● Stadium & Arenas Lighting 	- Available: single & double module configs