



Certifications:  
C3, Class I

ON REQUEST

Factory

Electrical Information					
Model No.	FL80	FL80	FL80	FL80	FL80
Power (±5%)	50W	100W	150W	200W	300W
Input Voltage	.	.	.	.	.
Power Factor	>0.9				
Driver Type	Constant current (CC)				
Control	.	.	.	.	.
Surge Protect.	.	.	.	.	.

Optic Information					
Efficacy	160 lm/W				
Luminous Flux	.	.	.	.	.
CCT	3000K, 4000K, 5000K				
CRI	Ra70 (Ra80 opt)				
Beam Angle	.	.	.	.	.

Description	Dimensions & Mount
essential ON/OFF floodlight, 50-300W.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>• IP66 &amp; IK07 double protection</li> <li>• Up to 160 lm/W efficacy</li> <li>• CCT adjustable: 3000K, 4000K, 5000K</li> <li>• Certified: C3, Class I</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>• Car Parks &amp; Plazas Lighting</li> <li>• Park &amp; City Centre Lighting</li> <li>• Auto Dealership Lighting</li> </ul>	<ul style="list-style-type: none"> <li>• 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>• Available: single &amp; double module configs</li> </ul>