



Certifications:  
IECEX (Ex db IIC T6/T5 Gb), ATEX, NEC&CEC C1

ON REQUEST

Factory

Electrical Information					
Model No.	HA03 Victory	HA03 Victory	HA03 Victory	HA03 Victory	HA03 Victory
Power (±5%)	30W	40W	50W	60W	70W
Input Voltage	.	.	.	.	.
Power Factor	>0.9				
Driver Type	Constant current (CC)				
Control	.	.	.	.	.
Surge Protect.	.	.	.	.	.

Optic Information					
Efficacy	140 lm/W				
Luminous Flux	.	.	.	.	.
CCT	5000K (2000K-6500K opt) / R/G/B/Amber				
CRI	Ra70 (Ra80 opt)				
Beam Angle	.	.	.	.	.

Description	Dimensions & Mount
Zone 1 / CID1 hazardous-area luminaire.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>IP66 &amp; IK10 double protection</li> <li>Up to 140 lm/W efficacy</li> <li>CCT adjustable: 5000K (2000K-6500K opt) /</li> <li>Certified: IECEX (Ex db IIC T6/T5 Gb), ATE</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>Explosion-proof Lighting</li> <li>Highly Corrosive Lighting</li> </ul>	- Available: single & double module configs