



Certifications:  
IECEX (Ex nR IIC T6/T5 Gc / Ex tb IIIC T80/95 Db)

ON REQUEST

Factory

| Electrical Information |                       |               |               |
|------------------------|-----------------------|---------------|---------------|
| Model No.              | HA04 150-240W         | HA04 150-240W | HA04 150-240W |
| Power (±5%)            | 150W                  | 200W          | 240W          |
| Input Voltage          | .                     | .             | .             |
| Power Factor           | >0.9                  |               |               |
| Driver Type            | Constant current (CC) |               |               |
| Control                | .                     | .             | .             |
| Surge Protect.         | .                     | .             | .             |

| Optic Information |                                       |   |   |
|-------------------|---------------------------------------|---|---|
| Efficacy          | 150 lm/W                              |   |   |
| Luminous Flux     | .                                     | . | . |
| CCT               | 5000K (2000K-6500K opt) / R/G/B/Amber |   |   |
| CRI               | Ra70 (Ra80 opt)                       |   |   |
| Beam Angle        | .                                     | . | . |

| Description                             | Dimensions & Mount                                 |
|---|--|
| Zone 2 / CID2 hazardous-area luminaire. | Material: Aluminum alloy<br>Finish: Powder coating |

| Key Features   | Lifespan & Warranty  |
|--|--|
| <ul style="list-style-type: none"> <li>● IP66 &amp; IK08 double protection</li> <li>● Up to 150 lm/W efficacy</li> <li>● CCT adjustable: 5000K (2000K-6500K opt) /</li> <li>● Certified: IECEX (Ex nR IIC T6/T5 Gc / Ex</li> </ul> | Operating Temp:<br>Lifespan: L70 - 50,000 hrs<br>Warranty: years |

| Applications  | New Features                                |
|---|---|
| <ul style="list-style-type: none"> <li>● Explosion-proof Lighting</li> <li>● Highly Corrosive Lighting</li> </ul> | - Available: single & double module configs |