



Certifications:
IECEX (Ex eb mb IIC T4 Gb / Ex tb IIIC T110 Db IP

ON REQUEST

Factory

Electrical Information			
Model No.	HA04 Premium	HA04 Premium	HA04 Premium
Power (±5%)	150W	200W	240W
Input Voltage	.	.	.
Power Factor	>0.9		
Driver Type	Constant current (CC)		
Control	.	.	.
Surge Protect.	.	.	.

Optic Information	
Efficacy	n/d lm/W
Luminous Flux	.
CCT	Warm to Cool White + RGB/Amber
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
Zone 2 / CID2 hazardous-area luminaire.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & IK08 double protection ● Up to n/d lm/W efficacy ● CCT adjustable: Warm to Cool White + RGB/A ● Certified: IECEX (Ex eb mb IIC T4 Gb / Ex 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Explosion-proof Lighting ● Highly Corrosive Lighting 	· Available: single & double module configs