



Certifications:
IECEX (Ex eb mb IIC T5 Gb / Ex tb IIIC T95 Db), A

ON REQUEST

Factory

Electrical Information						
Model No.	HA05 Conqueror	HA05 Conqueror	HA05 Conqueror	HA05 Conqueror	HA05 Conqueror	HA05 Conqueror
Power (±5%)	30W	100W	120W	150W	180W	200W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information	
Efficacy	n/d lm/W
Luminous Flux	.
CCT	5000K (2000K-6500K opt) / R/G/B/Amber
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
Zone 2 / CID2 explosion-proof lighting.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> IP66 & IK08 double protection Up to n/d lm/W efficacy CCT adjustable: 5000K (2000K-6500K opt) / Certified: IECEX (Ex eb mb IIC T5 Gb / Ex 	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> Explosion-proof Lighting Highly Corrosive Lighting 	- Available: single & double module configs