



Certifications:
IECEX (Ex eb mb IIC T5..T4 Gb / Ex tb IIIC T95..T1

ON REQUEST
Factory

Electrical Information		
Model No.	HA06 Premium	HA06 Premium
Power (±5%)	50W	100W
Input Voltage	.	.
Power Factor	>0.9	
Driver Type	Constant current (CC)	
Control	.	.
Surge Protect.	.	.

Optic Information	
Efficacy	n/d lm/W
Luminous Flux	.
CCT	Warm to Cool White + R/G/B/Amber
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
Zone 2 / CID2 explosion-proof luminaire.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> • IP66 & IK08 double protection • Up to n/d lm/W efficacy • CCT adjustable: Warm to Cool White + R/G/B • Certified: IECEX (Ex eb mb IIC T5..T4 Gb / 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> • Explosion-proof Lighting • Highly Corrosive Lighting 	· Available: single & double module configs