



Certifications:
IECEX (Ex eb mb IIC T5 Gb), ATEX, NEC&CEC C1

ON REQUEST
Factory

Electrical Information						
Model No.	HA06 Supernova	HA06 Supernova	HA06 Supernova	HA06 Supernova	HA06 Supernova	HA06 Supernova
Power (±5%)	20W	100W	30W	40W	50W	60W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information						
Efficacy	160 lm/W					
Luminous Flux
CCT	5000K (2000K-6500K opt) / R/G/B/Amber					
CRI	Ra70 (Ra80 opt)					
Beam Angle

Description	Dimensions & Mount
Zone 2 / CID2 explosion-proof luminaire.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> IP66 & IK08 double protection Up to 160 lm/W efficacy CCT adjustable: 5000K (2000K-6500K opt) / Certified: IECEX (Ex eb mb IIC T5 Gb), ATE 	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> Explosion-proof Lighting Highly Corrosive Lighting 	- Available: single & double module configs