



Certifications:  
IECEX (Ex db IIC T6 / Ex tb IIIC T80 Db), ATEX, CI

ON REQUEST  
Factory

Electrical Information						
Model No.	HA08	HA08	HA08	HA08	HA08	HA08
Power (±5%)	30W	100W	40W	50W	60W	75W
Input Voltage	.	.	.	.	.	.
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control	.	.	.	.	.	.
Surge Protect.	.	.	.	.	.	.

Optic Information	
Efficacy	n/d lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
explosion-proof lighting series.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>IP66 &amp; IK10 double protection</li> <li>Up to n/d lm/W efficacy</li> <li>CCT adjustable: 3000K, 4000K, 5000K</li> <li>Certified: IECEX (Ex db IIC T6 / Ex tb III)</li> </ul>	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>Explosion-proof Lighting</li> <li>Highly Corrosive Lighting</li> </ul>	<ul style="list-style-type: none"> <li>3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>Available: single &amp; double module configs</li> </ul>