



Certifications:
 NEC&CEC C1D1/C1D2/C2D1/C2D2/C3, NEMA 4X

ON REQUEST

Factory

Electrical Information						
Model No.	HA11 C1D1	HA11 C1D1	HA11 C1D1	HA11 C1D1	HA11 C1D1	HA11 C1D1
Power (±5%)	30W	100W	40W	50W	60W	80W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information	
Efficacy	n/d lm/W
Luminous Flux	.
CCT	White (3000K-6500K), Amber
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
hazardous-area lighting series.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> IP66 & IK09 double protection Up to n/d lm/W efficacy CCT adjustable: White (3000K-6500K), Amber Certified: NEC&CEC C1D1/C1D2/C2D1/C2D2/C3, 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> Explosion-proof Lighting Highly Corrosive Lighting 	<ul style="list-style-type: none"> 3 CCT adjustable (3000 / 4000 / 5000K) Available: single & double module configs