



Certifications:
CE, ROHS, CB, TUV GS, ENEC, C tick, SAA, LM7

ON REQUEST

Factory

Electrical Information						
Model No.	HB01	HB01	HB01	HB01	HB01	HB01
Power (±5%)	100W	120W	150W	200W	240W	300W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information	
Efficacy	140 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
100-300W, 160lm/W, low UGR, ENEC.	Dimensions: n/d Net Weight: n/d Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP65 & IK08, IK10 double protection ● Up to 140 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: CE, ROHS, CB, TUV GS, ENEC, C t 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Logistics & Warehouse Lighting ● Manufacturing Lighting ● Hangar & High Ceiling Mount 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs