



Certifications:
Red Dot Winner 2018, CE, ROHS, UL, DLC, SAA,

ON REQUEST

Factory

Electrical Information				
Model No.	HB06	HB06	HB06	HB06
Power (±5%)	100W	120W	150W	200W
Input Voltage
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control
Surge Protect.

Optic Information	
Efficacy	150 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
100-200W, 155lm/W, NSF food-grade, power selectable.	Dimensions: n/d Net Weight: n/d Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> IP66/IP69K & IK08, IK10 double protection Up to 150 lm/W efficacy CCT adjustable: 3000K, 4000K, 5000K Certified: Red Dot Winner 2018, CE, ROHS, 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> Food Processing Lighting Cold Storage Lighting Highly Corrosive Lighting 	<ul style="list-style-type: none"> 3 CCT adjustable (3000 / 4000 / 5000K) Available: single & double module configs