



Certifications:
ENEC, UGR 24

ON REQUEST
 Factory

Electrical Information		
Model No.	HB17	HB17
Power (±5%)	450W	600W
Input Voltage	.	.
Power Factor	>0.9	
Driver Type	Constant current (CC)	
Control	.	.
Surge Protect.	.	.

Optic Information		
Efficacy	140 lm/W	
Luminous Flux	.	.
CCT	3000K, 4000K, 5000K	
CRI	Ra70 (Ra80 opt)	
Beam Angle	.	.

Description	Dimensions & Mount
450-600W, 160lm/W, ENEC certified.	Dimensions: n/d Net Weight: 0.3kg Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP65 & IK08 double protection ● Up to 140 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: ENEC, UGR 24 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Hangar & High Ceiling Mount ● Stadium & Arenas Lighting ● Manufacturing Lighting 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs