



Certifications:
UGR<26

ON REQUEST

Factory

Electrical Information						
Model No.	HB18	HB18	HB18	HB18	HB18	HB18
Power (±5%)	30W	100W	120W	150W	200W	50W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information	
Efficacy	160 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
30-200W, 170lm/W, power selectable.	Dimensions: n/d Net Weight: n/d Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP65 & IK08 double protection ● Up to 160 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: UGR<26 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Logistics & Warehouse Lighting ● Manufacturing Lighting ● Hangar & High Ceiling Mount 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs