



Certifications:  
DIN 57710-13, UGR 19

ON REQUEST

Factory

Electrical Information				
Model No.	HB42	HB42	HB42	HB42
Power (±5%)	100W	120W	150W	200W
Input Voltage	.	.	.	.
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control	.	.	.	.
Surge Protect.	.	.	.	.

Optic Information	
Efficacy	170 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
100-200W, 160lm/W, UGR<22, power & CCT selectable.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP65 &amp; IK09 double protection</li> <li>● Up to 170 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Certified: DIN 57710-13, UGR 19</li> </ul>	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Logistics &amp; Warehouse Lighting</li> <li>● Manufacturing Lighting</li> <li>● Hangar &amp; High Ceiling Mount</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>