



Certifications:
 ENEC, UGR 25.6

ON REQUEST

Factory

Electrical Information				
Model No.	HB44	HB44	HB44	HB44
Power (±5%)	100W	120W	150W	200W
Input Voltage
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control
Surge Protect.

Optic Information				
Efficacy	150 lm/W			
Luminous Flux
CCT	3000K, 4000K, 5000K			
CRI	Ra70 (Ra80 opt)			
Beam Angle

Description	Dimensions & Mount
100-200W, 170/210lm/W options, power & CCT selectable, ENEC.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> • IP65 & IK08 double protection • Up to 150 lm/W efficacy • CCT adjustable: 3000K, 4000K, 5000K • Certified: ENEC, UGR 25.6 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> • Logistics & Warehouse Lighting • Manufacturing Lighting • Hangar & High Ceiling Mount 	<ul style="list-style-type: none"> • 3 CCT adjustable (3000 / 4000 / 5000K) • Available: single & double module configs