



Certifications:
C4 corrosion class, NSF

ON REQUEST

Factory

| Electrical Information | | | | |
|------------------------|-----------------------|------|------|------|
| Model No. | HB69 | HB69 | HB69 | HB69 |
| Power (±5%) | 100W | 120W | 150W | 180W |
| Input Voltage | . | . | . | . |
| Power Factor | >0.9 | | | |
| Driver Type | Constant current (CC) | | | |
| Control | . | . | . | . |
| Surge Protect. | . | . | . | . |

| Optic Information | |
|-------------------|---------------------|
| Efficacy | 165 lm/W |
| Luminous Flux | . |
| CCT | 3000K, 4000K, 5000K |
| CRI | Ra70 (Ra80 opt) |
| Beam Angle | . |

| Description | Dimensions & Mount |
|--|--|
| 100-180W, 165lm/W, NSF food-grade, IP69K, C4 anti-corrosion. | Material: Aluminum alloy Finish: Powder coating |

| Key Features | Lifespan & Warranty |
|--|--|
| <ul style="list-style-type: none"> IP69K & IK08, IK10 double protection Up to 165 lm/W efficacy CCT adjustable: 3000K, 4000K, 5000K Certified: C4 corrosion class, NSF | Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years |

| Applications | New Features |
|--|---|
| <ul style="list-style-type: none"> Food Processing Lighting Cold Storage Lighting Highly Corrosive Lighting Manufacturing Lighting | <ul style="list-style-type: none"> 3 CCT adjustable (3000 / 4000 / 5000K) Available: single & double module configs |