



Certifications:  
UGR<24

ON REQUEST

Factory

Electrical Information				
Model No.	HB73	HB73	HB73	HB73
Power (±5%)	100W	150W	200W	240W
Input Voltage	.	.	.	.
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control	.	.	.	.
Surge Protect.	.	.	.	.

Optic Information	
Efficacy	190 lm/W
Luminous Flux	.
CCT	4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
100-240W, 160/180/200lm/W options, power/CCT/beam selectable.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP65 &amp; IK08 double protection</li> <li>● Up to 190 lm/W efficacy</li> <li>● CCT adjustable: 4000K, 5000K</li> <li>● Certified: UGR&lt;24</li> </ul>	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Logistics &amp; Warehouse Lighting</li> <li>● Manufacturing Lighting</li> <li>● Hangar &amp; High Ceiling Mount</li> </ul>	- Available: single & double module configs