



Certifications:
DIN 57710-13, ENEC

ON REQUEST

Factory

Electrical Information						
Model No.	LHB09	LHB09	LHB09	LHB09	LHB09	LHB09
Power (±5%)	100W	150W	200W	240W	300W	400W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information						
Efficacy	160 lm/W					
Luminous Flux
CCT	3000K, 4000K, 5000K					
CRI	Ra70 (Ra80 opt)					
Beam Angle

Description	Dimensions & Mount
100-480W IP66 IK10 ball-proof linear high bay.	Dimensions: 680*325*60 Net Weight: 7KG Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & IK10 double protection ● Up to 160 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: DIN 57710-13, ENEC 	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Logistics & Warehouse Lighting ● Manufacturing Lighting ● Hangar & High Ceiling Mount 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs