



Certifications:
n/d

ON REQUEST

Factory

Electrical Information			
Model No.	LHB13	LHB13	LHB13
Power (±5%)	20W	40W	50W
Input Voltage	.	.	.
Power Factor	>0.9		
Driver Type	Constant current (CC)		
Control	.	.	.
Surge Protect.	.	.	.

Optic Information			
Efficacy	130 lm/W		
Luminous Flux	.	.	.
CCT	3000K, 4000K, 5000K		
CRI	Ra70 (Ra80 opt)		
Beam Angle	.	.	.

Description	Dimensions & Mount
plastic housing tri-proof luminaire.	Dimensions: n/d Net Weight: n/d Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66, IP69K & IK06, IK10 double protection ● Up to 130 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: n/d 	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Food Processing Lighting ● Cold Storage Lighting ● Highly Corrosive Lighting 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs