



Certifications:
n/d

ON REQUEST

Factory

Electrical Information			
Model No.	LHB26	LHB26	LHB26
Power (±5%)	40W	60W	75W
Input Voltage	.	.	.
Power Factor	>0.9		
Driver Type	Constant current (CC)		
Control	.	.	.
Surge Protect.	.	.	.

Optic Information			
Efficacy	150 lm/W		
Luminous Flux	.	.	.
CCT	3000K, 4000K, 5000K		
CRI	Ra70 (Ra80 opt)		
Beam Angle	.	.	.

Description	Dimensions & Mount
LEDiL lens trunking light.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP20 & IK04 double protection ● Up to 150 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: n/d 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Logistics & Warehouse Lighting ● Manufacturing Lighting ● Hangar & High Ceiling Mount 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs