



Certifications:  
n/d

ON REQUEST

Factory

Electrical Information			
Model No.	LHB42	LHB42	LHB42
Power (±5%)	100W	150W	200W
Input Voltage	.	.	.
Power Factor	>0.9		
Driver Type	Constant current (CC)		
Control	.	.	.
Surge Protect.	.	.	.

Optic Information			
Efficacy	170 lm/W		
Luminous Flux	.	.	.
CCT	5000K		
CRI	Ra70 (Ra80 opt)		
Beam Angle	.	.	.

Description	Dimensions & Mount
warehouse/rack luminaire with Zhaga & Casambi.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP65 &amp; IK08 double protection</li> <li>● Up to 170 lm/W efficacy</li> <li>● CCT adjustable: 5000K</li> <li>● Certified: n/d</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Logistics &amp; Warehouse Lighting</li> <li>● Manufacturing Lighting</li> <li>● Hangar &amp; High Ceiling Mount</li> </ul>	- Available: single & double module configs