



Certifications:  
C3, Class I, Zhaga

ON REQUEST

Factory

Electrical Information					
Model No.	PT10	PT10	PT10	PT10	PT10
Power (±5%)	30W	100W	120W	50W	75W
Input Voltage	.	.	.	.	.
Power Factor	>0.9				
Driver Type	Constant current (CC)				
Control	.	.	.	.	.
Surge Protect.	.	.	.	.	.

Optic Information	
Efficacy	140 lm/W
Luminous Flux	.
CCT	3000K, 4000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
geometric-design post-top lighting fixture.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>IP66 &amp; IK08 double protection</li> <li>Up to 140 lm/W efficacy</li> <li>CCT adjustable: 3000K, 4000K</li> <li>Certified: C3, Class I, Zhaga</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>Park &amp; City Centre Lighting</li> <li>Landscape Lighting</li> <li>Urban &amp; Residential Streets</li> </ul>	<ul style="list-style-type: none"> <li>3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>Available: single &amp; double module configs</li> </ul>