



Certifications:
PF >0.90

ON REQUEST

Factory

Electrical Information					
Model No.	SL01	SL01	SL01	SL01	SL01
Power (±5%)	30W	100W	40W	60W	80W
Input Voltage
Power Factor	>0.9				
Driver Type	Constant current (CC)				
Control
Surge Protect.

Optic Information					
Efficacy	195 lm/W				
Luminous Flux
CCT	3000K, 4000K, 5000K				
CRI	Ra70 (Ra80 opt)				
Beam Angle

Description	Dimensions & Mount
solar lighting with 4-6 nights autonomy.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & n/d double protection ● Up to 195 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: PF >0.90 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Coastal Solar Lighting ● Desert Solar Lighting ● Street & Roadway Lighting ● Urban & Residential Streets 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs