



Certifications:  
Corrosion Class C3, PF >0.94

ON REQUEST

Factory

Electrical Information				
Model No.	SL02	SL02	SL02	SL02
Power (±5%)	10W	20W	30W	40W
Input Voltage	.	.	.	.
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control	.	.	.	.
Surge Protect.	.	.	.	.

Optic Information	
Efficacy	160 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
openable solar streetlight up to 8000 lumens.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>• IP66 &amp; IK08 double protection</li> <li>• Up to 160 lm/W efficacy</li> <li>• CCT adjustable: 3000K, 4000K, 5000K</li> <li>• Certified: Corrosion Class C3, PF &gt;0.94</li> </ul>	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>• Coastal Solar Lighting</li> <li>• Desert Solar Lighting</li> <li>• Street &amp; Roadway Lighting</li> <li>• Urban &amp; Residential Streets</li> </ul>	<ul style="list-style-type: none"> <li>• 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>• Available: single &amp; double module configs</li> </ul>