



Certifications:
Class III, Corrosion Class C3

ON REQUEST

Factory

Electrical Information				
Model No.	SL03	SL03	SL03	SL03
Power (±5%)	20W	30W	40W	60W
Input Voltage
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control
Surge Protect.

Optic Information	
Efficacy	200 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
modular solar streetlight with 2-3 rainy-day autonomy.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> • IP66 & IK08 double protection • Up to 200 lm/W efficacy • CCT adjustable: 3000K, 4000K, 5000K • Certified: Class III, Corrosion Class C3 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> • Coastal Solar Lighting • Desert Solar Lighting • Street & Roadway Lighting • Urban & Residential Streets 	<ul style="list-style-type: none"> • 3 CCT adjustable (3000 / 4000 / 5000K) • Available: single & double module configs