



Certifications:  
n/d

ON REQUEST

Factory

Electrical Information	
Model No.	SL30-010
Power (±5%)	10W
Input Voltage	.
Power Factor	>0.9
Driver Type	Constant current (CC)
Control	Single strut
Surge Protect.	.

Optic Information	
Efficacy	170 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	Single strut

Description	Dimensions & Mount
3CCT selectable solar lighting with multiple mounting methods.	Material: Aluminum alloy Finish: Powder coating Color: Black

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP66 &amp; n/d double protection</li> <li>● Up to 170 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Single strut</li> <li>● Certified n/d</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Landscape Lighting</li> <li>● Park &amp; City Centre Lighting</li> <li>● Solar Sign Lighting</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>