



Certifications:  
n/d

**ON REQUEST**

Factory

Electrical Information					
Model No.	SP12	SP12	SP12	SP12	SP12
Power (±5%)	600W	1200W	1500W	1800W	750W
Input Voltage	.	.	.	.	.
Power Factor	>0.9				
Driver Type	Constant current (CC)				
Control	.	.	.	.	.
Surge Protect.	.	.	.	.	.

Optic Information	
Efficacy	180 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5700K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
sports and industrial high-power luminaire up to 180lm/W, adjustable mounting, 20kV surge protection, C5 anti-corrosion.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP66 &amp; IK08 double protection</li> <li>● Up to 180 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5700K</li> <li>● Certified: n/d</li> </ul>	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Stadium &amp; Arenas Lighting</li> <li>● Soccer &amp; Football Lighting</li> <li>● Baseball/Softball Field Lighting</li> <li>● Basketball Court Lighting</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>