



Certifications:
ENEC

ON REQUEST

Factory

Electrical Information						
Model No.	ST03	ST03	ST03	ST03	ST03	ST03
Power (±5%)	15W	120W	150W	20W	30W	50W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information	
Efficacy	140 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
30-150W Class I & II streetlight.	Dimensions: n/d Net Weight: n/d Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> • IP66 & IK08 double protection • Up to 140 lm/W efficacy • CCT adjustable: 3000K, 4000K, 5000K • Certified: ENEC 	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> • Street & Roadway Lighting • Urban & Residential Streets • Transportation Lighting 	<ul style="list-style-type: none"> • 3 CCT adjustable (3000 / 4000 / 5000K) • Available: single & double module configs