



Certifications:  
ENEC

ON REQUEST

Factory

Electrical Information						
Model No.	ST10	ST10	ST10	ST10	ST10	ST10
Power (±5%)	30W	120W	150W	180W	240W	300W
Input Voltage	.	.	.	.	.	.
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control	.	.	.	.	.	.
Surge Protect.	.	.	.	.	.	.

Optic Information	
Efficacy	145 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
30-300W roadway luminaire with tool-free opening.	Dimensions: 649x272x179mm Net Weight: 7.1 KG Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP66 &amp; IK08 double protection</li> <li>● Up to 145 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Certified: ENEC</li> </ul>	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Street &amp; Roadway Lighting</li> <li>● Transportation Lighting</li> <li>● Urban &amp; Residential Streets</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>