



Certifications:  
ENEC

ON REQUEST

Factory

| Electrical Information |                       |      |      |      |      |      |
|------------------------|-----------------------|------|------|------|------|------|
| Model No.              | ST33                  | ST33 | ST33 | ST33 | ST33 | ST33 |
| Power (±5%)            | 35W                   | 120W | 160W | 195W | 210W | 60W  |
| Input Voltage          | .                     | .    | .    | .    | .    | .    |
| Power Factor           | >0.9                  |      |      |      |      |      |
| Driver Type            | Constant current (CC) |      |      |      |      |      |
| Control                | .                     | .    | .    | .    | .    | .    |
| Surge Protect.         | .                     | .    | .    | .    | .    | .    |

| Optic Information |                     |
|-------------------|---------------------|
| Efficacy          | 140 lm/W            |
| Luminous Flux     | .                   |
| CCT               | 3000K, 4000K, 5000K |
| CRI               | Ra70 (Ra80 opt)     |
| Beam Angle        | .                   |

| Description   | Dimensions & Mount                                 |
|---|--|
| 30-200W roadway luminaire with tool-free opening and C4 anti-corrosion. | Material: Aluminum alloy<br>Finish: Powder coating |

| Key Features   | Lifespan & Warranty  |
|--|--|
| <ul style="list-style-type: none"> <li>● IP66 &amp; IK09 double protection</li> <li>● Up to 140 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Certified: ENEC</li> </ul> | Operating Temp:<br>Lifespan: L70 · 50,000 hrs<br>Warranty: years |

| Applications  | New Features  |
|---|---|
| <ul style="list-style-type: none"> <li>● Street &amp; Roadway Lighting</li> <li>● Transportation Lighting</li> <li>● Highly Corrosive Lighting</li> </ul> | <ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul> |