



Certifications:
 ENEC, Class I/II, 3G Rated

ON REQUEST

Factory

Electrical Information				
Model No.	ST38	ST38	ST38	ST38
Power (±5%)	40W	100W	60W	75W
Input Voltage
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control
Surge Protect.

Optic Information	
Efficacy	130 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
40-100W intelligent-control streetlight.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & IK08 double protection ● Up to 130 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: ENEC, Class I/II, 3G Rated 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Street & Roadway Lighting ● Urban & Residential Streets ● Transportation Lighting 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs