



Certifications:  
n/d

ON REQUEST

Factory

Electrical Information			
Model No.	ST43	ST43	ST43
Power (±5%)	10W	20W	30W
Input Voltage	.	.	.
Power Factor	>0.9		
Driver Type	Constant current (CC)		
Control	.	.	.
Surge Protect.	.	.	.

Optic Information			
Efficacy	200 lm/W		
Luminous Flux	.	.	.
CCT	3000K, 4000K, 5000K		
CRI	Ra70 (Ra80 opt)		
Beam Angle	.	.	.

Description	Dimensions & Mount
integrated solar roadway lighting with 3-4 nights autonomy.	Dimensions: 662X301X94mm Net Weight: 0.3kg Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP65 &amp; IK08 double protection</li> <li>● Up to 200 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Certified: n/d</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Coastal Solar Lighting</li> <li>● Desert Solar Lighting</li> <li>● Street &amp; Roadway Lighting</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>