



Certifications:

ENEC

ON REQUEST

Factory

| Electrical Information | | | |
|------------------------|-----------------------|------|------|
| Model No. | ST52 | ST52 | ST52 |
| Power (±5%) | 20W | 40W | 60W |
| Input Voltage | . | . | . |
| Power Factor | >0.9 | | |
| Driver Type | Constant current (CC) | | |
| Control | . | . | . |
| Surge Protect. | . | . | . |

| Optic Information | | | |
|-------------------|---------------------|---|---|
| Efficacy | 140 lm/W | | |
| Luminous Flux | . | . | . |
| CCT | 3000K, 4000K, 5000K | | |
| CRI | Ra70 (Ra80 opt) | | |
| Beam Angle | . | . | . |

| Description | Dimensions & Mount |
|---|--|
| 20-60W high-efficacy streetlight with optional low UGR. | Material: Aluminum alloy Finish: Powder coating |

| Key Features | Lifespan & Warranty |
|--|--|
| <ul style="list-style-type: none"> ● IP66 & IK09 double protection ● Up to 140 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: ENEC | Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years |

| Applications | New Features |
|---|---|
| <ul style="list-style-type: none"> ● Street & Roadway Lighting ● Urban & Residential Streets ● Park & City Centre Lighting | <ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs |