



Certifications:
n/d

ON REQUEST

Factory

Electrical Information						
Model No.	ST61	ST61	ST61	ST61	ST61	ST61
Power (±5%)	30W	100W	120W	150W	200W	240W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information	
Efficacy	160 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
30-480W high-power roadway luminaire, IK09, C4 anti-corrosion.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> • IP66 & IK09 double protection • Up to 160 lm/W efficacy • CCT adjustable: 3000K, 4000K, 5000K • Certified: n/d 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> • Street & Roadway Lighting • Transportation Lighting • Highly Corrosive Lighting 	<ul style="list-style-type: none"> • 3 CCT adjustable (3000 / 4000 / 5000K) • Available: single & double module configs