



Certifications:  
ENEC

ON REQUEST

Factory

Electrical Information						
Model No.	ST71	ST71	ST71	ST71	ST71	ST71
Power (±5%)	20W	100W	120W	150W	180W	200W
Input Voltage	.	.	.	.	.	.
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control	.	.	.	.	.	.
Surge Protect.	.	.	.	.	.	.

Optic Information						
Efficacy	190 lm/W					
Luminous Flux	.	.	.	.	.	.
CCT	3000K, 4000K					
CRI	Ra70 (Ra80 opt)					
Beam Angle	.	.	.	.	.	.

Description	Dimensions & Mount
20-300W, dual Zhaga, 190lm/W, selectable power/CCT.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>IP66 &amp; IK09 double protection</li> <li>Up to 190 lm/W efficacy</li> <li>CCT adjustable: 3000K, 4000K</li> <li>Certified: ENEC</li> </ul>	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>Street &amp; Roadway Lighting</li> <li>Transportation Lighting</li> <li>Urban &amp; Residential Streets</li> </ul>	<ul style="list-style-type: none"> <li>3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>Available: single &amp; double module configs</li> </ul>