



Certifications:
n/d

ON REQUEST

Factory

Electrical Information						
Model No.	ST72	ST72	ST72	ST72	ST72	ST72
Power (±5%)	20W	100W	120W	150W	200W	40W
Input Voltage
Power Factor	>0.9					
Driver Type	Constant current (CC)					
Control
Surge Protect.

Optic Information						
Efficacy	150 lm/W					
Luminous Flux
CCT	3000K, 4000K, 5000K					
CRI	Ra70 (Ra80 opt)					
Beam Angle

Description	Dimensions & Mount
20-200W cost-effective streetlight with glass optics, NEMA and Zhaga.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> ● IP66 & IK08 double protection ● Up to 150 lm/W efficacy ● CCT adjustable: 3000K, 4000K, 5000K ● Certified: n/d 	Operating Temp: Lifespan: L70 · 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> ● Street & Roadway Lighting ● Urban & Residential Streets ● Transportation Lighting 	<ul style="list-style-type: none"> · 3 CCT adjustable (3000 / 4000 / 5000K) · Available: single & double module configs