



Certifications:  
C4 corrosion (ISO 9223:2012), CE

ON REQUEST

Factory

Electrical Information				
Model No.	TN02	TN02	TN02	TN02
Power (±5%)	60W	120W	150W	90W
Input Voltage	.	.	.	.
Power Factor	>0.9			
Driver Type	Constant current (CC)			
Control	.	.	.	.
Surge Protect.	.	.	.	.

Optic Information	
Efficacy	155 lm/W
Luminous Flux	.
CCT	3000K, 4000K, 5000K
CRI	Ra70 (Ra80 opt)
Beam Angle	.

Description	Dimensions & Mount
C4 anti-corrosion tunnel luminaire.	Dimensions: 308x206x171mm Net Weight: 0.3kg Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP66 &amp; IK08 double protection</li> <li>● Up to 155 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Certified: C4 corrosion (ISO 9223:2012), C</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Tunnel Lighting</li> <li>● Transportation Lighting</li> <li>● Highly Corrosive Lighting</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>