



Certifications:  
Full Cut-off

ON REQUEST

Factory

Electrical Information		
Model No.	WP01	WP01
Power (±5%)	40W	70W
Input Voltage	.	.
Power Factor	>0.9	
Driver Type	Constant current (CC)	
Control	.	.
Surge Protect.	.	.

Optic Information		
Efficacy	140 lm/W	
Luminous Flux	.	.
CCT	3000K, 4000K, 5000K	
CRI	Ra70 (Ra80 opt)	
Beam Angle	.	.

Description	Dimensions & Mount
high-efficacy wall pack with low UGR option.	Dimensions: 296x150x223mm Net Weight: 0.3kg Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP65 &amp; IK10 double protection</li> <li>● Up to 140 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Certified: Full Cut-off</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Architectural Lighting</li> <li>● Logistics &amp; Warehouse Lighting</li> <li>● Manufacturing Lighting</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>