



Certifications:  
Full Cut-off

ON REQUEST

Factory

Electrical Information					
Model No.	WP08	WP08	WP08	WP08	WP08
Power (±5%)	15W	25W	35W	45W	55W
Input Voltage	.	.	.	.	.
Power Factor	>0.9				
Driver Type	Constant current (CC)				
Control	.	.	.	.	.
Surge Protect.	.	.	.	.	.

Optic Information					
Efficacy	120 lm/W				
Luminous Flux	.	.	.	.	.
CCT	3000K, 4000K, 5000K				
CRI	Ra70 (Ra80 opt)				
Beam Angle	.	.	.	.	.

Description	Dimensions & Mount
dark-sky wall pack solution.	Material: Aluminum alloy Finish: Powder coating

Key Features	Lifespan & Warranty
<ul style="list-style-type: none"> <li>● IP66 &amp; IK10 double protection</li> <li>● Up to 120 lm/W efficacy</li> <li>● CCT adjustable: 3000K, 4000K, 5000K</li> <li>● Certified: Full Cut-off</li> </ul>	Operating Temp: Lifespan: L70 - 50,000 hrs Warranty: years

Applications	New Features
<ul style="list-style-type: none"> <li>● Architectural Lighting</li> <li>● Landscape Lighting</li> <li>● Urban &amp; Residential Streets</li> </ul>	<ul style="list-style-type: none"> <li>· 3 CCT adjustable (3000 / 4000 / 5000K)</li> <li>· Available: single &amp; double module configs</li> </ul>